

Canon i-SENSYS MF4750

i-SENSYS Laser Multifunction Printers



Product Specification

- [TYPE](#)
- [PRINTER](#)
- [COPIER](#)
- [SCANNER](#)
- [FAX](#)
- [MEDIA HANDLING](#)
- [INTERFACE & SOFTWARE](#)
- [GENERAL FEATURES](#)
- [CONSUMABLES](#)
- [ACCESSORIES / OPTIONS](#)

TYPE

Machine Type	Mono Laser All-in-One
Available Functions	Print, Copy, Scan and Fax

PRINTER

Print Speed	Up to 23 ppm (A4)
Printing Method	Monochrome laser beam printing
Print Quality	Up to 1200 x 600 dpi with Automatic Image Refinement
Print Resolution	600 x 600 dpi
First Print Out Time	6 secs
Printer Languages	UFR II-LT
Print Margins	5 mm-top and bottom, 5 mm-left and right
Toner Saver Mode	Yes

COPIER

Copy Speed	Up to 23 ppm (A4)
First Copy Output Time (FCOT)	Approx. 9 seconds or less
Copy Resolution	Up to 600 x 600 dpi
Copy Modes	Text, Text/Photo, Text/Photo+, Photo
Multiple Copy	Up to 99 copies
Reduction / Enlargement	25-400% in 1% increments

Toner Saver Mode	Yes
Other Features	Memory sort, 2 on 1, 4 on 1, ID Card Copy

SCANNER

Type	Colour
Scan Resolution	Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi
Colour Scanning Depth	24 bit/24 bit (input/output)
Greyscales	256 levels
Compatibility	TWAIN, WIA
Max. Scan Width	216 mm

FAX

Modem Speed	Super G3 33.6kbps
Receive Mode	FAX Only, Manual, Answering, Fax / Tel Auto SW
Fax Resolution	Standard: 200 x 100 dpi Fine: 200 x 200 dpi Photo: 200 x 200 dpi Super fine: 200 x 400 dpi
FAX Memory	Up to 256 pages ¹
Speed Dials	Max. 103 (including 3 one-touch dials)
Group Dials/Destinations	Max. 102 destinations
Sequential Broadcast	Max. 113 locations
Memory Backup	Unlimited
Other Features	Dual Access, Remote RX, PC Fax (sending only), FAX Forwarding, DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports

MEDIA HANDLING

Scanner Type	Flatbed and Automatic Document Feeder (ADF)
Paper Input (Standard)	250-sheet tray 1-sheet manual feed slot 35-sheet ADF
Paper Output	100-sheet
Media Types	Plain, heavy, Recycled, Transparency, Label, Envelope
Media Sizes	Tray: A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard Envelope: COM10, Monarch, C5, DL, Custom sizes: Min. 76.2 x 210mm to Max. 216 x 356mm Manual feed slot: A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard Envelope: COM10, Monarch, C5, DL, Custom sizes (Min. 76.2 x 127mm to Max. 216 x 356mm) ADF: A4, B5, A5, B6, LTR, LGL

	Min. 105 x 148mm to Max. 356 x 216mm
Media Weights	Tray: 60 to 163 g/m ² Manual feed slot: 60 to 163 g/m ²

INTERFACE & SOFTWARE

Interface Type	USB 2.0 Hi-speed
Operating System Compatibility	Windows 7/ XP/ Vista Mac OS X Version 10.4.9 - and up ² Linux ^{2 3}
Software and Printer Management	Printer driver, Fax driver, Scanner driver, MF Toolbox, AddressBookTool, Presto! PageManager

GENERAL FEATURES

Duty Cycle	Max. 10,000 pages per month
Warm-up Time	Approx. 13.5 seconds from power on
Memory	128 MB
Control Panel	5 lines BW LCD
Dimensions with Trays (W x D x H)	390 mm x 439 mm x 360 mm
Installation Space (W x D x H)	426 mm x 555 mm x 623 mm
Weight	11.9 Kg
Operating Environment	Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)
Power Source	220-240 V (±10%), 50/60 Hz (±2 Hz)
Power Consumption	Maximum: Approx. less than 1320 W Active: Approx. less than 560 W Stand by mode: Approx. 5 W Sleep mode: Approx. 1.4 W Typical Electricity Consumption (TEC): 0.7 kWh/week
Noise Levels	Sound Pressure Active: 50 dB(A) or less Standby: Inaudible

CONSUMABLES

Cartridges	Cartridge 728 (2,100 pages ¹) ²
-------------------	--

ACCESSORIES / OPTIONS

Items	TELEPHONE KIT 6
--------------	-----------------

FAX Memory	¹ Based on ITU-T Standard Chart No. 1
Operating System Compatibility	¹ Web distribution only ² Web distribution only ³ Linux support printing only
Cartridges	¹ Based on ISO/IEC 19752 ² Ships with 1,000 pages starter cartridge

- All specifications subject to change without notice