# **LQ-2090IIN**

# **DATASHEET / BROCHURE**





Fast, networked 24-pin, 136-column dot matrix printer that offers outstanding reliability and an extremely low TCO.

The LQ-2090IIN is a high-volume dot matrix printer designed for fast and reliable printing. Upgrade your existing dot matrix printers to our latest model, which is now Energy Star compliant, and delivers built-in network capability with an incredibly low TCO.

# Fast print speed

The LQ-2090IIN offers an improved USD (ultra speed draft) speed of 550 characters per second at 10 characters per inch, making a real difference to high-volume print runs such as stock reports and large batches of invoices or freight documents.

### Increased reliability

Epson's dot matrix technology is already mature and very reliable. Building on this, the new printer improves the mean time between failure by 25% to 25,000 power-on hours, ideal for challenging conditions or where regular maintenance is not practical.

#### Same consumables

This printer uses the same ribbons as existing models, so you can upgrade your hardware and continue to use your current ribbon supplies.

#### **Network capability**

This is a network model which supports both serial and Ethernet connections for enhanced connectivity.

# **KEY FEATURES**

- Fast print speed
   USD speed of 550 characters per second at 10 characters per inch
- Increased reliability
   Mean time between failure of 25,000
   power-on hours
- Increased number of copies Now original plus six copies
- Network capability
   Supports both serial and Ethernet connections
- Same consumables
   Uses the same ribbons as existing models



#### PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method Impact dot matrix
Number of Pins 24 pins
Number of columns
Needles 24 Needles

PRINT

Printing Speed Ultra Speed-Draft: 10 cpi: 550 chars/s

Barcodes Code 128, Code 39, EAN-13, EAN-8, Interleaved 2 of 5, POSTNET, UPC-A, UPC-E

Carbon Copies 6 plus one original

CONNECTIVITY

Interfaces Hi-Speed USB - compatible with USB 2.0 specification, Parallel, Ethernet interface (100 Base-

TX / 10 Base-T

PAPER / MEDIA HANDLING

Document Feed Single sheet front and rear, Continuous paper front and rear, Paper output rear

Paper Formats Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels

(single- and multi-layer), Envelopes, Cardboard

Paper Thickness Continuous 0.12 mm - 0.46 mm

Pape

Paper Thickness Label Base 0.16 mm - 0.19 mm

Sheet

Paper Thickness Multi Part 0.12 mm - 0.46 mm Paper Thickness Single Sheet 0.065 mm - 0.14 mm

GENERAL

Energy Use 49 W

Product dimensions 612 x 375 x 177 mm (Width x Depth x Height)

Product weight 9.4 kg

Temperature Operation 5° C - 35° C Humidity Operation 10% - 80%

Compatible Operating Windows 10, Windows 7, Windows 8, Windows Vista, Windows XP

Systems

Mean Time Between Failures 25,000 Hours

Print Head Life 400 Million Strokes/Wire Sound Pressure Operation: 55 dB (A) Noise Level Operation: 55 dB (A)

OTHER FEATURES

Input Data Buffer 128 kB

OTHER

Warranty 12 months Carry in

Optional warranty extension available

# **SUPPLIES**

• Epson SIDM Black Ribbon Cartridge for LQ-2090 (C13S015336) C13S015336

#### **OPTIONAL ACCESSORIES**

 Wide Pull Tractor Unit FX-2190II/LQ-2090II C12C933791

 Epson SIDM Push/pull tractor unit for FX-2190, LQ-2090 C12C800212

# LOGISTICS INFORMATION

SKU	C11CF40402A1
EAN code	8715946651392
Country of Origin	Indonesia
Layer	2 Units

For more information please contact:

Telephone: 01952 607111 (UK)+ 01 436 7742 (Republic of Ireland) E-mail: enquiries@epson.co.uk Chat: etalk.epson-europe.com Fax: 0871 222 6740 + Local call rate.

Web: www.epson.co.uk www.epson.ie

#### **LQ-2090IIN**

# WHAT'S IN THE BOX

- User manual
- Driver and utilities (CD)
- Ribbon
- Power cable

